

## PRESS RELEASE

# Kverneland Taarup 9469 S

02.09.2010, Gottmadingen, Germany



*Kverneland 9469 S VARIO*

*By adding many new features Kverneland has started the generation change going from the 90xx series to the new 94xx series on its rake range. On the two models Kverneland Taarup 9469 S EVO and 9469 S VARIO all these features are included, leading to a higher capacity, better raking performance and easier operation.*

### **Kverneland Taarup 9469 S – One Machine – Two Executions**

The new 9469 S is a double rotor side delivery rake based on the main frame concept which is available in two executions:

- The EVO model which is capable of making one swath to the side, raking up to 6.90 m into one swath
- The VARIO execution can in addition make two single swathes, leading to a working width of 7.70 m. By hydraulically extending the two lift arms, the overlap between the two rotors is eliminated and two swathes can be placed along each of the rotors. A swath board for the front rotor comes standard with this machine.

### **Raking Performance and Operational Comfort**

The new rotor gearbox with optimized cam track shape and tine arm control is resulting in a better swath forming and swath shape, leading to increased raking capacity.

The main frame and the rotor undercarriage of the machine have been redesigned and now provide an improved ground contour following under difficult conditions.

In addition many details, such as tine arm storage position, height adjustment of the rotors, steering rods, etc. have been improved in order to give maximum comfort to the user.

### TerraLink Quattro Ground Contour Following

The unique key feature, which allows the rotors to adapt perfectly to all ground contours. It enables the rotor to float in 3 dimensions and gives a perfect raking result under all working conditions. In combination with the Quattro undercarriage with which 4 wheels are running close to the tines, this system maximizes the possible working speed while at the same time ensuring clean and loss free raking. Soil contamination of the grass is minimized at the same time.

### Technical Specifications:

	<b>9469 S EVO</b>	<b>9469 S VARIO</b>
Working width	6.90 m	6.90 / 7.70 m
Transport height	3,15* / 4,00 m	3,15* / 4,00 m
Transport width	2,85 m	2,85 m
Tine arms per rotor	11/12	11/12
Tines per arm	4/5	4/5
Weight	1.700 kg	1.900 kg

\* with detached tine arms

\*\*\*

Kverneland Group (Kverneland ASA - OSE: KVE) is a leading international company developing, producing and distributing agricultural machinery and services. Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package of systems and solutions to the professional farming community. The offering covers soil preparation, seeding, forage- and bale equipment, spreading and spraying. For more information on Kverneland Group visit [www.kvernelandgroup.com](http://www.kvernelandgroup.com)

-- END --

For Details, Contact:

Uwe Kellermeier, Product Director, Mowers, Haytools & Wagons  
 Kverneland Group Gottmadingen  
 Tel. +49 7731 788 300  
 Email: [uwe.kellermeier@kvernelandgroup.com](mailto:uwe.kellermeier@kvernelandgroup.com)