

PRESS RELEASE

Vicon Rake Andex 724-764

02.09.2010, Gottmadingen, Germany



Vicon Andex 764

By adding many new features, Vicon has started the generation change going from the -03 series to the new -04 series on its rake range. On the new models Andex 724 and 764 all these features are included and are leading to a higher capacity, better raking performance and easier operation.

Andex 724 and 764 – The Universal Machines

- The new Andex 724 is a double rotor centre swath rake based on the main frame concept and offers an adjustable working width from 6.20 m up to 7.20 m and a corresponding swath width of 1.20 to 1.90 m.
- The new Andex 764 is based on the same concept with an adjustable working width from 7.00 m up to 7.80 m and a corresponding swath width of 1.30 to 1.90 m.

This makes the machines suitable for work in front of any kind of harvesting machine with narrow or wide pick ups.

The adjustment can be done hydraulically from the tractor cab.

Raking Performance and Operational Comfort

The new rotor gear box with optimized cam track shape and tine arm control is resulting in a better swath forming and swath shape, by increased raking capacity.

The main frame and the rotor undercarriage of the machines have been redesigned and now provide an improved ground contour following under difficult circumstances.

In addition many details, such as tine arm storage position, height adjustment of the rotors, steering rods, etc. have been improved in order to give maximum comfort to the user.

TerraLink Quattro Ground Contour Following

The unique key feature, which allows the rotors to adapt perfectly to any ground contours. It enables the rotor floating in 3 dimensions and gives a perfect raking result under all working conditions. In combination with the Quattro undercarriage which 4 wheels are running closest to the tines this system maximizes the possible working speed by at the same time ensuring clean and loss free raking. Soil contamination of the grass is minimized at the same time.

Technical Specifications:

	Andex 724	Andex 764
Working width	6.20 – 7.20 m,	7.00 – 7.80 m,
Transport height	3,75 m	3,50* / 4,10 m
Transport width	2,85 m	2,85 m
Tine arms per rotor	11	11
Tines per arm	4	4
Weight	1.600 kg	1.640 kg

* with detached tine arms

Kverneland Group (Kverneland ASA - OSE: KVE) is a leading international company developing, producing and distributing agricultural machinery and services. Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package of systems and solutions to the professional farming community. The offering covers soil preparation, seeding, forage- and bale equipment, spreading and spraying. For more information on Kverneland Group visit www.kvernelandgroup.com

-- END --

For Details, Contact:

Uwe Kellermeier, Product Director, Mowers, Haytools & Wagons

Kverneland Group Gottmadingen

Tel. +49 7731 788 300

Email: uwe.kellermeier@kvernelandgroup.com