

PRESS RELEASE

Vicon Rake Andex 694

02.09.2010, Gottmadingen, Germany



Andex 694 VARIO

By adding many new features Vicon has started the generation change going from the -03 series to the new -04 series on its rake range. On the two models Andex 694 EVO and Andex 694 VARIO all these features are included, leading to a higher capacity, better raking performance and easier operation.

Andex 694 – One Machine – Two Executions

The new Andex 694 is a double rotor side delivery rake based on the main frame concept which is available in two executions:

- The EVO model which is capable of making one swath to the side, raking up to 6.90 m into one swath
- The VARIO execution can in addition make two single swaths, leading to a working width of 7.70 m. By hydraulically extending the two lift arms, the overlap between the two rotors is eliminated and two swathes can be placed along each of the rotors. A swath board for the front rotor comes standard with this machine.

Raking Performance and Operational Comfort

The new rotor gearbox with optimized cam track shape and tine arm control is resulting in a better swath forming and swath shape, leading to increased raking capacity.

The main frame and the rotor undercarriage of the machine have been redesigned and now provide an improved ground contour following under difficult conditions. In addition many details, such as tine arm storage position, height adjustment of the rotors, steering rods, etc. have been improved in order to give maximum comfort to the user.

TerraLink Quattro Ground Contour Following

The unique key feature, which allows the rotors to adapt perfectly to all ground contours. It enables the rotor to float in 3 dimensions and gives a perfect raking result under all working conditions. In combination with the Quattro undercarriage with which 4 wheels are running close to the tines, this system maximizes the possible working speed while at the same time ensuring clean and loss free raking. Soil contamination of the grass is minimized at the same time.

Technical Specifications:

	Andex 694 EVO	Andex 694 VARIO
Working width	6.90 m	6.90 / 7.70 m
Transport height	3,15* / 4,00 m	3,15* / 4,00 m
Transport width	2,85 m	2,85 m
Tine arms per rotor	11/12	11/12
Tines per arm	4/5	4/5
Weight	1.700 kg	1.900 kg

* with detached tine arms

Kverneland Group (Kverneland ASA - OSE: KVE) is a leading international company developing, producing and distributing agricultural machinery and services. Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package of systems and solutions to the professional farming community. The offering covers soil preparation, seeding, forage- and bale equipment, spreading and spraying. For more information on Kverneland Group visit www.kvernelandgroup.com

- - END - -

For Details, Contact:

Uwe Kellermeier, Product Director, Mowers, Haytools & Wagons
 Kverneland Group Gottmadingen
 Tel. +49 7731 788 300
 Email: uwe.kellermeier@kvernelandgroup.com